

## In Technical Collaboration with IMT Serbia

## IMATEUII Power Tractor





The Power Accompanies with...

- **EUROPEAN TECHNOLOGY**
- **DURABLE & FUEL EFFICIENT**
- **POWER STEERING**
- HEAVY DUTY FRONT AXLE
- **SPRING SUSPENSION SEAT**
- **™** 12 MONTHS / 1200 HRS WARRANTY\*
- NATIONWIDE AFTER SALES SERVICE
- NATIONWIDE SPARE PARTS AVAILABILITY

\* WHICHEVER EARLIEI

## TECHNICAL SPECIFICATIONS OF IMT-577 76 HP TRACTOR

ENGINE		STEERING	
Engine Power	76 PS	Туре	Hydrostatic
Compression	16 ratio 1	IP .	
Гуре	IMR-S44 A/T	REAR AXLE & BRAKES	
Number of Cylinder	4	Brake Type	Oil Immersed, Multi Disc
Bore	100.96mm	Actuation	Hydraulic
Stroke	127mm	Axel Type	Straddle with Epicyclic Reduction Unit
Capacity	4.068 Lt	Parking Brake	Hand Lever Operated
Aspiration	Natural	Differential Lock	Mechanical
Starting	Thermostart	and the second	•
Throttle Control	Foot & Hand	INSTRUMENTATION	
Cooling	Water		Tachometer, Hourmeter, Fuel
Air Cleaner Type	Oil Bath	Gauges	Level, Battery Condition, & Water
Air Pre Cleaner	Over Bonnet		Temperature
Fuel Filter	Duel, High Capacity	Warning Lights	Elect Charge, Low Engine Oil Level,
Exhaust	Vertical		Oil Pressure, Turn Indicators, Head
000			Light Main Beam & Auxiliary Socket.
	ELECTRIC	TULL POWER	- A A
Voltage	12 V, Negative Earth	TYRES	
Battery	120Ah	Front	7.50-16, 6PR
Starter Motor	3 Kw	Rear	16.9/14-30, 6PR
Alternator	45 Amp.		
		WHEEL TRACK	
CLUTCH		Front	1300-1900 mm
Туре	Duel Clutch, Dry Disc	Rear	1400-2100 mm
4 11111		Final Company Company	
TRANSMISSION		OVERALL DIMENSIONS	
Туре	Manual, Sliding	Length	3690 mm
Number of Gears	8 Forward, 2 Reverse	Width	1960 mm
200		Height	2490 mm
POWER TAKE OFF		Road Clearance	484 mm
Туре	Live		
Engine Speed at 540 PTO rpm	1789 rpm		WEIGHT
Shaft Diameter	35 mm	Gross Weight	2300 Kg
Number of Spline	6		-
			CAPACITIES
HYDRAULICS		Fuel Tank	108 Lt
Function	Position Control, Draft Control,	Engine Oil Sump	7.6 Lt
	Response Control, Constant Pumping	Transmission /Hydraulic	36.5
Туре	Reciprocating	Reservoir, Steering Oil	2.1 Lt
Lower Links	Cat I & II, Interchangeable	Oil Bath, Air Cleaner	0.7 Lt
		Cooling System	15.4 Lt

## ORIENT AUTOMOTIVE INDUSTRIES (PVT) LTD

Note:



Head Office: Suite No. 416, Continental Trade Centre, Block-8, Clifton, Karachi - Pakistan Ph No.: +92 21 35302913, 35302902-3 Fax No. +92 21 35303063

Email: info@orientautomotive.com.pk Web: www.orientautomotive.com.pk

Plant : Plot No. A1 to A50, Nazar Chowrangi, Hub Industrial Trading Estate (HITE), Hub- Pakistan

- OAIL reserves the right to change specifications without prior notice.
- The above mentioned values for power and torque are according to manufacturer's standards.