BULL POWER 560 S (60HP) (Power Steering)



Technical Specifications

EN	NGINE
Engine power	60.8HP
Compression Ratio	16.0:1
Type	IMR-DM 34 T
Number Of Cylinder	3
Bore	91.4mm
Stroke	127mm
Capacity	2.5 Ltr.
Aspiration	Turbo Charged
Starting Aid	Thermo start
Throttle Control	Foot & Hand
Cooling	Water
Air Cleaner Type	Oil Bath
Air Pre Cleaner	Over Bonnet
Fuel Filter	Dual, High Capacity
Exhaust	Vertical
Oil Cooler	Air Cooled
Injection	Direct
Injection	ECTRIC
Voltage	12V, Negative Earth
Battery	120 Ah
Starter Motor	2.2 kW
A decision of the second of th	32 Amp
Alternator	
	UTCH
Туре	Dual Clutch, Disc
TRANSMISSION	
Type	Sliding Super Gear
Number of Gears	8 Forward, 2 Reverse
POWER TAKE OFF (PTO)	
Туре	
	Live
Engine Speed at 540 PTO rpm	Live 1789 rpm
Engine Speed at 540 PTO rpm	1789 rpm
Engine Speed at 540 PTO rpm Shaft Diameter Number of Splines	1789 rpm 35 mm 6
Engine Speed at 540 PTO rpm Shaft Diameter Number of Splines	1789 rpm 35 mm 6 RAULICS
Engine Speed at 540 PTO rpm Shaft Diameter Number of Splines	1789 rpm 35 mm 6 RAULICS Position Control, Draft Control,
Engine Speed at 540 PTO rpm Shaft Diameter Number of Splines HYD Function	1789 rpm 35 mm 6 RAULICS Position Control, Draft Control, Response Control, Constant Pumping
Engine Speed at 540 PTO rpm Shaft Diameter Number of Splines	1789 rpm 35 mm 6 RAULICS Position Control, Draft Control,
Engine Speed at 540 PTO rpm Shaft Diameter Number of Splines HYD Function Type lower Links	1789 rpm 35 mm 6 RAULICS Position Control, Draft Control, Response Control, Constant Pumping Reciprocating
Engine Speed at 540 PTO rpm Shaft Diameter Number of Splines HYD Function Type lower Links Oil Flow (Max)	1789 rpm 35 mm 6 RAULICS Position Control, Draft Control, Response Control, Constant Pumping Reciprocating Cat I & II 16 L/min
Engine Speed at 540 PTO rpm Shaft Diameter Number of Splines HYD Function Type lower Links Oil Flow (Max) STE	1789 rpm 35 mm 6 RAULICS Position Control, Draft Control, Response Control, Constant Pumping Reciprocating Cat I & II 16 L/min EERING
Engine Speed at 540 PTO rpm Shaft Diameter Number of Splines HYD Function Type lower Links Oil Flow (Max) STE	1789 rpm 35 mm 6 RAULICS Position Control, Draft Control, Response Control, Constant Pumping Reciprocating Cat I & II 16 L/min EERING Hydrostatic
Engine Speed at 540 PTO rpm Shaft Diameter Number of Splines HYD Function Type lower Links Oil Flow (Max) STE Type	1789 rpm 35 mm 6 RAULICS Position Control, Draft Control, Response Control, Constant Pumping Reciprocating Cat I & II 16 L/min EERING Hydrostatic LE & BRAKES
Engine Speed at 540 PTO rpm Shaft Diameter Number of Splines HYD Function Type lower Links Oil Flow (Max) STE Type REAR AXI Brake Type	1789 rpm 35 mm 6 RAULICS Position Control, Draft Control, Response Control, Constant Pumping Reciprocating Cat I & II 16 I/min BERING Hydrostatic E & BRAKES Oil immersed, Disc Brake
Engine Speed at 540 PTO rpm Shaft Diameter Number of Splines HYD Function Type lower Links Oil Flow (Max) STE Type REAR AXI Brake Type Actuation	1789 rpm 35 mm 6 RAULICS Position Control, Draft Control, Response Control, Constant Pumping Reciprocating Cat I & II 16 L/min EERING Hydrostatic LE & BRAKES Oil immersed, Disc Brake Mechanical
Engine Speed at 540 PTO rpm Shaft Diameter Number of Splines HYD Function Type lower Links Oil Flow (Max) STE Type REAR AXI Brake Type	1789 rpm 35 mm 6 RAULICS Position Control, Draft Control, Response Control, Constant Pumping Reciprocating Cat I & II 16 I/min BERING Hydrostatic E & BRAKES Oil immersed, Disc Brake

Differential Lock	Mechanical
INSTRUMENT PANEL (DASH BOARD)	
TOP	Tachometer, Hour Meter, Fuel Gauge,
Gauges	Battery Condition, & Water
- O A	Temperature
	Battery Charge, Low Engine oil
Warning Lights	Pressure, Indicators, Head Light, Main
	Beam & Auxiliary Socket
TYRE	
Front	7.50 -16, 6PR
Rear	14.9/13-28, 6PR
TRACK ADJUSTMENT	
Front	1245-1854 mm
Rear	1420-2130 mm
OVERALL DIMENSIONS	
Length	3260 mm
Width	1890 mm
Height	2235 mm
Ground Clearance	394 mm
WEIGHT	
Gross Weight	1950 Kg
CAPACITIES (LTR.)	
Fuel Tank	50 Ltr.
Engine Oil Sump	6.9 Ltr.
Transmission/Hydraulic	35.9 Ltr.
Steering Box	0.9 Ltr.
Oil Bath Air Cleaner	0.5 Ltr.
Cooling System	10.5 Ltr.

Standard Equipments

- Chain stabilizer
- **Check chains**
- Spring suspension seat
- Flat top fenders
- Standard tool box with set of tools
- Weight frame

Optional Equipment

- Front End wheels
- Draw bar
- Canopy

Note: Orient Automotive industries Pvt. Ltd. deserves all rights to change specification without prior notice