

BULL POWER PRIME MOVER PM-3-50 (50HP)



Technical Specifications

ENGINE	
Engine power	50HP
Model	PM-3-50
Type	Diesel
Number Of Cylinder	3 in-line
Bore	91.4mm
Stroke	127mm
Capacity	2.5 Ltr.
Aspiration	Natural
Configuration	4 Cycle Vertical
Cooling	Water Cooled
Direction of Rotation	Clockwise - Viewed from front
Power take-off	From Flywheel End
Exhaust	Vertical

OUTPUT	
2250 RPM	50.0 HP
2200 RPM	48.5 HP
2000 RPM	46.0 HP
1800 RPM	42.5 HP
1500 RPM	38.0 HP

OVERALL DIMENSIONS	
Length	1230 mm
Width	1110 mm
Height	1250 mm

CAPACITIES (LTR.)	
Fuel Tank	45 Ltr.
Engine Oil Sump	6.8 Ltr.
Cooling System	10.2 Ltr.

STANDARD EQUIPMENT

Clutching / Declutching with lever

12V Alternator

Panel mounted on base frame complete with:

- (a) Tacho meter
- (b) Hour meter
- (c) Ammeter
- (d) Low Oil Pressure Gauge
- (e) Water Temperature Gauge
- (f) Battery Charging
- (g) Ignition Key Switch

Note: Orient Automotive industries Pvt. Ltd. deserves all rights to change specification without prior notice